

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a REPORT SECURITY CLASSIFICATION

Unclassified

1b RESTRICTIVE MARKINGS

2a SECURITY CLASSIFICATION AUTHORITY

3 DISTRIBUTION / AVAILABILITY OF REPORT

2b. DECLASSIFICATION / DOWNGRADING SCHEDULE

PERFORMING ORGANIZATION REPORT NUMBER(S)

DOD POP HMT/AYD 89-005

5 MONITORING ORGANIZATION REPORT NUMBER(S)

NAME OF PERFORMING ORGANIZATION

ARDEC

6b. OFFICE SYMBOL
(If applicable)
SMCAR-AEP

7a. NAME OF MONITORING ORGANIZATION

ADDRESS (City, State, and ZIP Code)

Picatinny Arsenal, NJ 07806-5000

7b. ADDRESS (City, State, and ZIP Code)

NAME OF FUNDING / SPONSORING ORGANIZATION

8b. OFFICE SYMBOL
(If applicable)

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

ADDRESS (City, State, and ZIP Code)

10. SOURCE OF FUNDING NUMBERS

PROGRAM
ELEMENT NO.

PROJECT
NO.

TASK
NO.

WORK UNIT
ACCESSION NO.

11. TITLE (Include Security Classification)

Performance Oriented Packaging Testing of Bulk Propellant in New Fiber Drum

12. PERSONAL AUTHOR(S)

NAJAFI, NEZAM

13a. TYPE OF REPORT

Final

13b. TIME COVERED

FROM _____ TO _____

14. DATE OF REPORT (Year, Month, Day)

89-07-19

15. PAGE COUNT

16. SUPPLEMENTARY NOTATION

17. COSATI CODES

FIELD	GROUP	SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

Performance Oriented Packaging, POP, 21 Gal
Fiber Drum Container

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

This report contains the testing and test results performed on bulk propellant in New Fiber Drum.

DISTRIBUTION STATEMENT A

Approved for public release
Distribution Unlimited

DTIC
ELECTE
AUG 02 1989
D^{cy} D

20. DISTRIBUTION / AVAILABILITY OF ABSTRACT

☐ UNCLASSIFIED/UNLIMITED ☒ SAME AS RPT ☐ DTIC USERS

21. ABSTRACT SECURITY CLASSIFICATION

Unclassified

22a. NAME OF RESPONSIBLE INDIVIDUAL

NAJAFI, NEZAM

22b TELEPHONE (Include Area Code)

(201) 724-2935

22c. OFFICE SYMBOL

SMCAR-AEP

DD Form 1473, JUN 86

Previous editions are obsolete.

SECURITY CLASSIFICATION OF THIS PAGE

Unclassified

89

013

I. REPORT NUMBER: DODPOHMTTR/AYD89-005

II. TITLE: PERFORMANCE ORIENTED PACKAGING TESTING OF BULK PROPELLANT
IN 21 GAL FIBER DRUM CONTAINER

AUTHOR: NEZAM NAJAFI

PERFORMING ACTIVITY: ARDEC

ADDRESS: Department of the Army
Armament Research, Development and Engineering Center
HQ, US Army Armament, Munitions and Chemical Command
Picatinny Arsenal, New Jersey 07806-5000

DATE: 19 July 1989

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED

Accession For	
NTIS CRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



1. DATA SHEET

CONTAINER:

TYPE: FIBER DRUM

UN CODE: 1G

NOMENCLATURE: DRUM, FIBER (FOR BULK PROPELLANT)

SPECIFICATION: N/A

DRAWING NUMBER: 9342857

MATERIAL: CONVOLUTED FIBER WALLS/STEEL CHIMES

CAPACITY: 21 GALLONS

DIMENSION: 16.380 INCHES - OD X 27.63 INCHES - LENGTH

PRODUCT:

NAME: BULK PROPELLANT (M30)

SPECIFICATION NUMBER: MIL-STD-652D

STOCK NUMBER: 1376010539359

PHYSICAL STATE: SOLID

2. BACKGROUND

→ This report contains the testing and test results performed on M30 bulk cannon propellant packed in a 21-gallon fiber drum. The testing was performed exclusively using live M30 bulk propellant packed into a fiber drum for Performance Oriented Packaging (POP) certification. Live propellant was used in lieu of inert propellant or sand, etc, since this live propellant would more closely represent the actual materials to be packed in this drum. For example, this propellant is representative of all bulk cannon propellant in accordance with MIL-STD-652. Therefore, based upon these tests, it is intended to qualify all bulk cannon propellant per MIL-STD-652 by analogy in this new 21-gallon fiber drum. Tests were performed in accordance with Performance Oriented Packaging test regulations. ←

3. TEST

Six fiber drums packed with M30 bulk propellant were dropped from 4 feet (1.2 meters) in accordance with UN requirements. Drums were dropped on a 5-inch solid steel plate reinforced by 33 inches of concrete at two different orientations. The first 3 packed fiber drums were dropped once each from 4 feet (1.2 meters) at 45 degrees on the bottom chime at ambient. Then, the 3 remaining fiber drums were dropped once each from 4 feet (1.2 meters) at 45 degrees on the bottom chime at ambient.

4. RESULTS

The fiber drums passed all tests. None of the contents of the drums were discharged or spilled. They are considered safe for international transportation in accordance with Performance Oriented Packaging Regulations.

REFERENCE MATERIAL: United Nations "Transport of Dangerous Goods", Fourth Edition